MINI3 COLOR

Channel Letter LED Module



MINI3 Yellow

- Versatile wide angle lens with compact design
- Ensures excellent transmittance and uniform lighting
- 150 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 100 lm/W
- · Easy installation with double sided 3M tape
- IP68 Waterproof and approved by UL, CE, RoHS
- 5 year limited warranty











DESCRIPTION

DURITE MINI3 Series is Specialized for Channel Letter Signs.

The LED is powered by Reliable LED that makes high performance and durability as Tier 1 LED.

Starux's most cost-efficient model and easy installation with double sided 3M tape.

The ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

COVERAGE CHART

Model	MINI3-YLYG48	
Colors	Yellow	Max
Lumens	38.4 lm/mod (153.6 lm/ft)	Max
Efficacy	80 lm/W	Modu
Power	0.48 W/mod (1.92 W/ft)	Stan
Input Voltage	12V DC	Max
Beam Angle	150°	Parame
Modules/ft	4 mods/ft	
Dimensions	1.18" x 0.35" x 0.32"	DIM
Packaging	300 mods/bag (75 ft), 3000 mods/carton (750 ft)	DIM
Max in series	50 mods	
Operating Temp.	-4°F ~ 140°F / -20°C ~ 60°C	0.2 (7.4mi
Warranty	5 year	
IP Rating	IP68 Waterproof	0.3 (9mr

Depth	3"	4"	5"		
Max Stroke Single Row	6"	8"	10"		
Max Stroke Multi Rows	6"	8"	10"		
Modules per ft	4 mods per ft				
Standard Run	50 mods				
Max Run	50 mods				
Parameters can be adjusted according to the desired brightness.					

DIMENSIONS

