



PRO3 Regular 1.1W

- · Ensures excellent transmittance and uniform lighting
- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 100 lm/W
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- Advanced performance with guaranteed even brightenss
- 5 year limited warranty











DESCRIPTION

DURITE PRO is a new premium model for LED professionals.

PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance.

The extra size cover of 3M tape makes easy installation and saving labor cost.

Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

CO	VERA	GE	CHARI	

Model	PR03-40HL11	PR03-50HL11		
Colors	4000K	5000K		
Lumens	110 lm/mod (220 lm/ft)			
Efficacy	100 lm/W			
Power	1.1 W/mod (2.2 W/ft)			
Input Voltage 12V DC				
Beam Angle	160°			
Modules/ft	2 mods/ft			
Dimensions	2.76" × 0.67" × 0.4"			
Packaging	100 mods/bag (50 ft), 1200 mods/carton (600 ft)			
Max in series		nods		
Operating Temp.	-4°F ~ 140°F / -20°C ~ 60°C			
Warranty 5 year				
IP Rating	IP68 Waterproof			

Depth	4"	5"	6"	7"~10"		
Max Stroke Single Row	8"	10"	12"	14"		
Max Stroke Multi Rows	6"	10"	12"	14"		
Modules per ft	2 mods per ft					
Standard Run	50 mods					
Max Run	50 mods					
Parameters can be adjusted according to the desired brightness.						

DIMENSIONS

