PRO3 COLOR





PRO3 Colors 0.72W

- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 160 lm/W(PRO3 HE)
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- · Advanced performance with guaranteed even brightenss
- 5 year limited warranty











DESCRIPTION

DURITE PRO is a new premium model for LED professionals.

PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance.

The extra size cover of 3M tape makes easy installation and saving labor cost.

Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

Model	PR03-RESM72	PRO3-GRSM72	PRO3-BLSM72		
Colors	Red	Green	Blue		
Lumens	23.76 lm/mod (47.52 lm/ft)	51.12 lm/mod (102.24 lm/ft)	13.68 lm/mod (27.36 lm/ft)		
Efficacy	33 lm/W	71 lm/W	19 lm/W		
Power	0.72 W/mod (1.44 W/ft)				
Input Voltage		12V DC			
Beam Angle		160°			
Modules/ft		2 mods/ft			
Dimensions	2.76" x 0.67" x 0.4"				
Packaging	100 mods/bag (50 ft), 1200 mods/carton (600 ft)				
Max in series		50 mods			
Operating Temp.	-4°F ~ 140°F / -20°C ~ 60°C				
Warranty		5 year			
IP Rating	IP68 Waterproof				

COVERAGE CHART

Depth	3"	4"	5"	6"~8"		
Max Stroke Single Row	8"	10"	12"	14"		
Max Stroke Multi Rows	6"	10"	12"	14"		
Modules per ft	2 mods per ft					
Standard Run	50 mods					
Max Run	50 mods					
Parameters can be adjusted according to the desired brightness.						

DIMENSIONS

