DURITE PR03







PRO3 Regular 1.1W

- · Ensures excellent transmittance and uniform lighting
- 160 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 100 lm/W
- Easy installation with extra size cover of 3M tape and screw hole
- IP68 Waterproof and approved by UL, CE, RoHS
- Best LED solution for Channel Letter and Sign Box illumination
- Advanced performance with guaranteed even brightenss
- 5 year limited warranty

COVERAGE CHART



DESCRIPTION

DURITE PRO is a new premium model for LED professionals.

PRO is powered by Tier 1 LED with the enhanced lens and wire for highest performance.

The extra size cover of 3M tape makes easy installation and saving labor cost.

Our ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

SPECIFICATIONS

Model	PR03-30HL11	PR03-65HL11	PR03-10HL11	Depth	4"	5"	6"	7"~10"
Colors	3000K	6500K	10000K	Max Stroke Single Row	8"	10"	12"	14"
Lumens	11	0 lm/mod (220 lm/	Max Stroke Multi Rows	6"	10"	12"	14"	
Efficacy		100 lm/W	Modules per ft	2 mods per ft				
Power	1.1 W/mod (2.2 W/ft)			Standard Run	50 mods			
Input Voltage		12V DC	Max Run	50 mods				
Beam Angle	160°			Parameters can be adjusted according to the desired brightness.				
Modules/ft		2 mods/ft						
Dimensions		2.76" x 0.67" x 0.4"	DIMENCIONO					
Packaging	100 mods/bag (50 ft), 1200 mods/carton (600 ft)			DIMENSIONS				
Max in series		50 mods			6.02" (153n	nm)		
Operating Temp.	-4°F	= ~ 140°F / -20°C ~ 6						
Warranty	5 year			2.76" (70mm) 3.27" (83mm) 2.76" (70mm)				
IP Rating	IP68 Waterproof							